

**SPERRY 4T SM SAE 20W-40**

**Application**

One compartment engine gear clutch oil for motorcycles and scooters

**Benefits**

- Superior oxidation stability to prevent oil thickening in air cooled design engines of Indian motorcycles
- Special viscosity balance to confirm smooth clutch operation
- Excellent extreme pressure behaviour for long gear life

**Specification**

- JASO MA 2
- APISM

**Test description**

Tests	UOM	Method	Results
Appearance	----	Visual	Clear & Bright
Density @ 29.5°C	g/cm <sup>3</sup>	ASTM D 4052	0.8552
Colour		ASTM D 1500	L3.0
Kinematic Viscosity @ 40°C	cSt	ASTM D 445	110.62
Kinematic Viscosity @ 100°C	cSt	ASTM D 445	15.00
Viscosity Index	----	ASTM D 2270	142
Flash Point (COC)	°C	ASTM D 92	240
Pour Point	°C	ASTM D 97	-36
Foam Stability Test Seq I	ml/ml	ASTM D 892	0/0
Seq II	ml/ml	ASTM D 892	0/0
Seq III	ml/ml	ASTM D 892	0/0

**SPERRY ENGINEERING PVT. LTD.**

142-143, Jawahar Co-operative Ind. Estate, Opp. McDonald, Kamothe (Kalamboli),  
Panvel - 410 209. MH, INDIA • Tel : 022-27431845/49  
Email: care@sperryengineering.com • www.sperryengineering.com

Manufacturing plant Quality System | Laboratory Quality System  
ISO 9000, ISO 14000, ISO 18000 | ISO 17025