

SPERRY AXLE SAE 85W-140

Description :

Oil for mechanical transmissions of commercial vehicles, tractors & agricultural machinery. It is suitable for use in gears and differentials with hypoid gears wherever lubrication with Extreme Pressure characteristics is required.

Characteristics :

- Excellent E.P. properties for excellent protection even in extreme conditions.
- High anti-foaming and demulsifying characteristics for superior heat removal.

Specifications :

- SAE 85W-140
- API GL-5
- MIL-L-2105 D
- ZF-TE-ML-05A, 07A, 16D, 17B, 19B

Test descripon

Tests	UOM	Method	Results
Appearance	----	Visual	Clear & Bright
Density @ 29.5°C	Kg/L	ASTM D 4052	0.90
Colour	----	ASTM D 1500	L3.5
Kinematic Viscosity @ 40°C	cSt	ASTM D 445	Reported
Kinematic Viscosity @ 100°C	cSt	ASTM D 445	29
Viscosity Index	----	ASTM D 2270	100
Flash Point (COC)	°C	ASTM D 92	220
Pour Point	°C	ASTM D 97	-21

Above values are typical indicative.

SPERRY ENGINEERING PVT. LTD.

142-143, Jawahar Co-operative Ind. Estate, Opp. McDonald, Kamothe (Kalamboli),
Panvel - 410 209. MH, INDIA • Tel : 022-27431845/49
Email: care@sperryengineering.com • www.sperryengineering.com

Manufacturing plant Quality System
ISO 9000, ISO 14000, ISO 18000

Laboratory Quality System
ISO 17025