

SPERRY HD CF-4 15W-40

Application

Diesel engine oil applicable for Euro 1 and Euro 2 emission requirements in stationary and automotive applications trucks, mini trucks, SUVs etc

Benefits

- Able to use in turbo and naturally aspirated engines
- No deposits on turbo shafts
- Provides clean piston ring grooves in high temperature operations

Specification

- API CF-4
- MB 228.1
- SAE 15W-40

Test description

Tests	UOM	Method	Results
Appearance	----	Visual	Clear & Bright
Density @ 29.5°C	g/cm ³	ASTM D 4052	0.8620
Colour		ASTM D 1500	L3.0
Kinematic Viscosity @ 40°C	cSt	ASTM D 445	117.7
Kinematic Viscosity @ 100°C	cSt	ASTM D 445	14.84
Viscosity Index	----	ASTM D 2270	130
Flash Point (COC)	°C	ASTM D 92	234
Pour Point	°C	ASTM D 97	-39
TBN, mg KOH/g	mg KOH/gm	ASTM D2896B	6.70

Above values are typical indicative.

SPERRY ENGINEERING PVT. LTD.

142-143, Jawahar Co-operative Ind. Estate, Opp. McDonald, Kamothe (Kalamboli),
Panvel - 410 209. MH, INDIA • Tel : 022-27431845/49
Email: care@sperryengineering.com • www.sperryengineering.com

Manufacturing plant Quality System | Laboratory Quality System
ISO 9000, ISO 14000, ISO 18000 | ISO 17025