

**SPERRY TM 90 SAE 80W-90**

**Application**

SPERRY TM 90 SAE 80W-90 is an extreme pressure gear and transmission oil applicable for use in transmissions, transaxles and differentials of cars and light commercial vehicles and agricultural equipment.

**Benefits**

- Excellent resistance to effects of temperature ageing in continuous application use.
- Resistance to foam induction due to air entry and is able to maintain fluid film free of foam in such cases.
- Excellent corrosion protection and demulsibility capabilities.

**Specification**

- API GL-4
- US MIL-L-2105
- SAE 80W-90

**Test description**

Tests	UOM	Method	Results
Appearance	----	Visual	Clear & Bright
Density @ 29.5°C	Kg/L	ASTM D 4052	0.8914
Colour	----	ASTM D 1500	L3.0
Kinematic Viscosity @ 40°C	cSt	ASTM D 445	170.04
Kinematic Viscosity @ 100°C	cSt	ASTM D 445	15.60
Viscosity Index	----	ASTM D 2270	93
Flash Point (COC)	°C	ASTM D 92	228
Pour Point	°C	ASTM D 97	-27

Above values are typical indicative.

**SPERRY ENGINEERING PVT. LTD.**

142-143, Jawahar Co-operative Ind. Estate, Opp. McDonald, Kamothe (Kalamboli), Panvel - 410 209. MH, INDIA • Tel : 022-27431845/49  
 Email: care@sperryengineering.com • www.sperryengineering.com

Manufacturing plant Quality System | Laboratory Quality System  
 ISO 9000, ISO 14000, ISO 18000 | ISO 17025